

11 GPM: D25RE09

Product Specifications

To order now call 081-564-8315

Dilution Range:	1:1000 to 1:112 (.1 to .9%)
Water Flow Range:	0.05 to 11 GPM
Operating Pressure Range:	4.3 to 85 PSI
Available Housing Materials:	Polyacetal (Standard Blue)PVDF (White)
Dimensions:	14" x 6 1/4"
Weight:	4 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104° F
Included Accessories:	6 ft clear suction tube, strainer, weight, mounting bracket and operating manual
Recommended Accessories:	200 mesh filter, check valve, pressure regulator, flow restrictor.



Recommended Installation

IPK34 - 10 GPM Industrial Plumbing Kit



- 3/4" polypropylene ball valve 1/2" stainless steel ball valve 3/4" poly 200 mesh tee filter
- 3/4" brass pressure regulator w/gauge
- 3/4" 10 GPM flow restrictor
- 3/4" polypropylene check valve
- 3/4" union schedule 80 PVC
- 3/4" x 2" polypropylenefittings
- 1/2" x 2" polypropylene fitting
- 1/2" x 1/2" barb fitting
- 3/4" male to 1/2" female reducer bushing
- 3/4" T
- 3/4" street elbows
- Roll of Teflon tape
- Instruction card
- Zip tie





Dosatron Thailand Wang Daeng Industrial Supplies Co.,Ltd

116/98 Moo3, T.Bowin A.Sriracha Chonburi 20230 THAILAND Tel: (038) 337-838-9 Fax: (038) 337-840 www.WANGDEX.com