



## Safety Data Sheet

Page 1 of 14

LOCTITE SF 7471 BO1.75FOE/S

SDS No. : 153556

V001.13

Revision: 14.01.2025

printing date: 05.04.2025

### Section 1. Identification of the substance/preparation and of the company/undertaking

**Product name:**

LOCTITE SF 7471 BO1.75FOE/S

**Other means of identification:**

LOCTITE SF 7471 BO1.75FOE/S

**Product code:**

IDH135285

**Recommended use of the chemical and restrictions on use**

**Intended use:**

Activator

**Manufacturer/Importer/Distributor Representative Company**

Henkel Thailand Ltd. The Offices at Centralworld,  
35th Floor, 999/9 Rama 1 Rd.,  
Kwang Patumwan, Khet Patumwan,  
10330 Bangkok

Thailand

Phone: +66 (2209) 8000

Fax-no.: +66 (2209) 8008

**E-mail address of person responsible for Safety Data Sheet:**

ap-ua-psra.sea@henkel.com

**Emergency Telephone for Chemical Accidents:**

FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +662 209 8008

### Section 2. Hazards identification

**GHS Classification:**

**Hazard Class**

Flammable liquids  
Serious eye damage/eye irritation  
Skin sensitizer  
Specific target organ toxicity -  
single exposure  
Chronic hazards to the aquatic  
environment

**Hazard Category**

Category 2  
Category 2  
Category 1  
Category 3  
Category 3

**Target organ**

Central nervous system

**GHS label elements:**

**Hazard pictogram:**



---

**Signal word:**

Danger

**Hazard statement:**

H225 Highly flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

**Precaution:**

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Response:**

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

**Storage:**

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

**Disposal:**

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

<b>Section 3. Composition / information on ingredients</b>
--

**Substance or Mixture:**

Mixture

**Declaration of hazardous chemical:**

Hazard component CAS-No.	Content	GHS Classification
acetone 67-64-1	60- 100 %	Flammable liquids 2 H225 Serious eye damage/eye irritation 2A H319 Specific target organ toxicity - single exposure 3 H336
Propan-2-ol 67-63-0	10- 30 %	Flammable liquids 2 H225 Serious eye damage/eye irritation 2A H319 Specific target organ toxicity - single exposure 3 H336 Aspiration hazard 2 H305
2,2'-[(4-methylphenyl)imino]bisethanol 3077-12-1	1- 10 %	Acute toxicity 4; Oral H302 Serious eye damage/eye irritation 1 H318 Skin sensitizer 1 H317 Acute hazards to the aquatic environment 3 H402 Chronic hazards to the aquatic environment 3 H412
benzothiazole-2-thiol 149-30-4	0.1- 1 %	Acute toxicity 5; Oral H303 Skin sensitizer 1 H317 Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410

**Section 4. First aid measures****Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

**Skin contact:**Rinse with running water and soap.  
Seek medical advice.**Eye contact:**

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

**Ingestion:**Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.  
Seek medical advice.**Indication of immediate medical attention and special treatment needed:**

See section: Description of first aid measures

**Section 5. Fire fighting measures****Suitable extinguishing media:**

Carbon dioxide, foam, powder

**Improper extinguishing media:**

None known

**Special protection equipment and precautions for firefighters:**

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Hazardous combustion products:**

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

**Additional fire fighting advice:**

In case of fire, keep containers cool with water spray.

## Section 6. Accidental release measures

**Personal precautions:**

Avoid skin and eye contact.

Ensure adequate ventilation.

**Environmental precautions:**

Do not let product enter drains.

**Clean-up methods:**

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

## Section 7. Handling and storage

**Handling:**

Use only in well-ventilated areas.

Vapours should be extracted to avoid inhalation.

Keep away from sources of ignition - no smoking.

Avoid skin and eye contact.

**Storage:**

Refer to Technical Data Sheet.

Storage at 8 to 28°C is recommended.

Store in a cool, dry place.

**Section 8. Exposure controls / personal protection**

Components with specific control parameters for workplace:

ACETONE 67-64-1	<b>Value type</b>	Time Weighted Average (TWA):
	<b>ppm</b>	250
	<b>Remarks</b>	ACGIH
ACETONE 67-64-1	<b>Value type</b>	Time Weighted Average (TWA):
	<b>ppm</b>	1,000
	<b>Remarks</b>	TH OEL
ACETONE 67-64-1	<b>Value type</b>	Short Term Exposure Limit (STEL):
	<b>ppm</b>	500
	<b>Remarks</b>	ACGIH
2-PROPANOL 67-63-0	<b>Value type</b>	Time Weighted Average (TWA):
	<b>ppm</b>	200
	<b>Remarks</b>	ACGIH
ISOPROPYL ALCOHOL (IPA) 67-63-0	<b>Value type</b>	Time Weighted Average (TWA):
	<b>ppm</b>	400
	<b>Remarks</b>	TH OEL
2-PROPANOL 67-63-0	<b>Value type</b>	Short Term Exposure Limit (STEL):
	<b>ppm</b>	400
	<b>Remarks</b>	ACGIH

**Respiratory protection:**

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

**Hand protection:**

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

**Eye protection:**

Wear protective glasses.

Protective eye equipment should conform to EN166.

**Body protection:**

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

**Engineering controls:**

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

**General protection and hygiene measures:**

The workplace should be equipped with an emergency shower and eye-rinsing facility.

**Hygienic measures:**

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Take off contaminated clothing and wash before reuse.

## Section 9. Physical and chemical properties

<b>Appearance:</b>	Amber to yellowish liquid
<b>Odor:</b>	Acetone
<b>Odor threshold (CA):</b>	No data available.
<b>pH:</b> (Concentration: 100 % product)	5 - 6
<b>Melting point / freezing point:</b>	Not applicable, Product is a liquid
<b>Specific gravity:</b>	0.7953
<b>Boiling point:</b>	56 °C (132.8 °F)
<b>Flash point:</b>	-8 °C (17.6 °F)
	Estimated
<b>Evaporation rate:</b>	No data available.
<b>Flammability (solid, gas):</b>	No data available.
<b>Lower explosive limit:</b>	2.6 %(V)
<b>Upper explosive limit:</b>	12.8 %(V)
<b>Vapor pressure:</b>	172 mm hg
	(; 20 °C (68 °F))
<b>Vapor density:</b>	2
<b>Density:</b>	0.795 g/cm3
<b>Solubility:</b>	Miscible
<b>Partition coefficient: n-octanol/water:</b>	No data available.
<b>Auto ignition:</b>	Not applicable
<b>Decomposition temperature:</b>	No data available.
<b>Viscosity:</b>	No data available.
<b>VOC content:</b>	98.5 %
	(2010/75/EC)

## Section 10. Stability and reactivity

**Reactivity/Incompatible materials:**

Reaction with strong acids.

Reacts with strong oxidants.

**Chemical stability:**

Stable under recommended storage conditions.

**Conditions to avoid:**

Stable

**Hazardous decomposition products:**

Irritating organic vapours.

**Section 11. Toxicological information**

**Oral toxicity:** Acute toxicity estimate (ATE) : > 2,000 mg/kg  
Method: Calculation method

Symptoms of Overexposure: EYE: Irritation, conjunctivitis.  
Prolonged or repeated contact may cause skin irritation.  
Vapors may cause drowsiness and dizziness.

**Acute oral toxicity:**

acetone 67-64-1	Value type	LD50
	Value	5,800 mg/kg
	Species	rat
	Method	not specified
Propan-2-ol 67-63-0	Value type	LD50
	Value	5,840 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
2,2'-[(4-methylphenyl)imino]bisethanol 3077-12-1	Value type	LD50
	Value	959 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
benzothiazole-2-thiol 149-30-4	Value type	LD50
	Value	2,830 mg/kg
	Species	rat
	Method	not specified

**Acute inhalative toxicity:**

acetone 67-64-1	Value type	LC50
	Value	76 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified
benzothiazole-2-thiol 149-30-4	Value type	LC50
	Value	> 1,270 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified

**Acute dermal toxicity:**

acetone 67-64-1	Value type	LD50
	Value	> 15,688 mg/kg
	Species	rabbit
	Method	Draize Test
Propan-2-ol 67-63-0	Value type	LD50
	Value	12,870 mg/kg
	Species	rabbit
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
2,2'-[(4-methylphenyl)imino]bisethanol 3077-12-1	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
benzothiazole-2-thiol 149-30-4	Value type	LD50
	Value	> 7,940 mg/kg
	Species	rabbit
	Method	not specified

**Skin corrosion/irritation:**

acetone 67-64-1	Result	not irritating
	Exposure time	
	Species	guinea pig
	Method	not specified
Propan-2-ol 67-63-0	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2,2'-[(4-methylphenyl)imino]bisethanol 3077-12-1	Result	not irritating
	Exposure time	24 h
	Species	rabbit
	Method	not specified

**Serious eye damage/irritation:**

acetone 67-64-1	Result	irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Propan-2-ol 67-63-0	Result	Category 2A (irritating to eyes)
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2,2'-[(4-methylphenyl)imino]bisethanol 3077-12-1	Result	Category 1 (irreversible effects on the eye)
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)



**Respiratory or skin sensitization:**

acetone 67-64-1	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	not specified
Propan-2-ol 67-63-0	Result	not sensitising
	Test type	Buehler test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
2,2'-(4-methylphenyl)imino]bisethanol 3077-12-1	Result	sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
benzothiazole-2-thiol 149-30-4	Result	sensitising
	Test type	Buehler test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
benzothiazole-2-thiol 149-30-4	Result	sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

acetone 67-64-1	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
acetone 67-64-1	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
acetone 67-64-1	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
acetone 67-64-1	Result	negative
	Type of study / Route of administration	oral: drinking water
	Metabolic activation / Exposure time	
	Species	mouse
	Method	not specified
Propan-2-ol 67-63-0	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propan-2-ol 67-63-0	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Propan-2-ol 67-63-0	Result	negative
	Type of study / Route of administration	intraperitoneal
	Metabolic activation / Exposure time	
	Species	mouse
	Method	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
benzothiazole-2-thiol 149-30-4	Result	negative
	Type of study / Route of administration	intraperitoneal
	Metabolic activation / Exposure time	
	Species	mouse
	Method	Micronucleus assay

**Repeated dose toxicity:**

acetone 67-64-1	Result	NOAEL=900 mg/kg
	Route of application	oral: drinking water
	Exposure time / Frequency of treatment	13 wdaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Propan-2-ol 67-63-0	Result	
	Route of application	inhalation: vapour
	Exposure time / Frequency of treatment	104 w6 h/d, 5 d/w
	Species	rat
	Method	OECD Guideline 451 (Carcinogenicity Studies)
benzothiazole-2-thiol 149-30-4	Result	NOAEL=375 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	13 weeks5 days/week
	Species	rat
	Method	not specified
benzothiazole-2-thiol 149-30-4	Result	LOAEL=750 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	13 weeks5 days/week
	Species	rat
	Method	not specified

**Section 12. Ecological information****General ecological information:**

Do not empty into drains / surface water / ground water.

**Ecotoxicity:**

H412 Harmful to aquatic life with long lasting effects.

**Toxicity:**

acetone 67-64-1	Value type	LC50
	Value	8,120 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
acetone 67-64-1	Value type	EC50
	Value	8,800 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia pulex
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
acetone 67-64-1	Value type	NOEC
	Value	530 mg/l
	Acute Toxicity Study	Algae
	Exposure time	8 d
	Species	Microcystis aeruginosa
	Method	DIN 38412-09
acetone 67-64-1	Value type	EC10
	Value	1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	Pseudomonas putida
	Method	DIN 38412, part 27 (Bacterial oxygen consumption test)
Propan-2-ol 67-63-0	Value type	LC50
	Value	> 9,640 - 10,000 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)

Propan-2-ol 67-63-0	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	1,000 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
2,2'-(4-methylphenyl)imino]bisethanol 3077-12-1	Value type	LC50
	Value	> 100 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Cyprinus carpio
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
2,2'-(4-methylphenyl)imino]bisethanol 3077-12-1	Value type	EC50
	Value	48 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2,2'-(4-methylphenyl)imino]bisethanol 3077-12-1	Value type	EC50
	Value	> 100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-(4-methylphenyl)imino]bisethanol 3077-12-1	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge of a predominantly domestic sewage
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
benzothiazole-2-thiol 149-30-4	Value type	LC50
	Value	0.73 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
	Value type	NOEC
	Value	0.041 mg/l
	Acute Toxicity Study	Fish
	Exposure time	89 d
	Species	Oncorhynchus mykiss
	Method	other guideline:
benzothiazole-2-thiol 149-30-4	Value type	EC50
	Value	0.71 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
benzothiazole-2-thiol 149-30-4	Value type	EC50
	Value	0.5 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)

	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	0.066 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)
benzothiazole-2-thiol 149-30-4	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC50
	Value	3,301 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

**Persistence and degradability:**

acetone 67-64-1	Result	readily biodegradable
	Route of application	aerobic
	Degradability	81 - 92 %
	Method	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
Propan-2-ol 67-63-0	Result	readily biodegradable
	Route of application	aerobic
	Degradability	70 - 84 %
	Method	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
2,2'-[(4-methylphenyl)imino]bisethanol 3077-12-1	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	1.5 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
benzothiazole-2-thiol 149-30-4	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	2.5 %
	Method	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))

**Bioaccumulative potential / Mobility in soil:**

acetone 67-64-1	LogPow	-0.24
	Temperature	
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Propan-2-ol 67-63-0	LogPow	0.05
	Temperature	
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
2,2'-[(4-methylphenyl)imino]bisethanol 3077-12-1	LogPow	2
	Temperature	35 °C
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
benzothiazole-2-thiol 149-30-4	Bioconcentration factor (BCF)	< 8
	Exposure time	6 Weeks
	Species	Cyprinus carpio
	Temperature	
	Method	other guideline:
benzothiazole-2-thiol 149-30-4	LogPow	2.34 - 2.5
	Temperature	
	Method	not specified

### Section 13. Disposal considerations

#### Product

**Method of disposal:**

Dispose of in accordance with local and national regulations.

#### Packaging

**Disposal of uncleaned packages:**

Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

### Section 14. Transport information

**Road transport ADR:**

Class:	3
Packing group:	II
Classification code:	F1
Hazard ident. number:	33
UN no.:	1993
Label:	3
Technical name:	FLAMMABLE LIQUID, N.O.S. (Acetone,Isopropanol)
Additional information:	Special provision 640D

**Railroad transport RID:**

Class:	3
Packing group:	II
Classification code:	F1
Hazard ident. number:	33
UN no.:	1993
Label:	3
Technical name:	FLAMMABLE LIQUID, N.O.S. (Acetone,Isopropanol)
Additional information:	Special provision 640D

**Inland water transport ADN:**

Class:	3
Packing group:	II
Classification code:	F1
Hazard ident. number:	33
UN no.:	1993
Label:	3
Technical name:	FLAMMABLE LIQUID, N.O.S. (Acetone,Isopropanol)
Additional information:	Special provision 640D

**Marine transport IMDG:**

Class:	3
Packing group:	II
UN no.:	1993
Label:	3
EmS:	F-E ,S-E
Seawater pollutant:	-
Proper shipping name:	FLAMMABLE LIQUID, N.O.S. (Acetone,Isopropanol)

**Air transport IATA:**

Class:	3
Packing group:	II
Packaging instructions (passenger):	353
Packaging instructions (cargo):	364
UN no.:	1993
Label:	3
Proper shipping name:	Flammable liquid, n.o.s. (Acetone,Isopropanol)

## Section 15. Regulatory information

**Regulatory Information:**

Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

**Global inventory status:**

Regulatory list	Notification
TSCA	yes
DSL	yes
KECI (KR)	yes
ENCS (JP)	yes
ISHL (JP)	yes
IECSC	yes
AIIC	yes
NZIOC	yes
TCSI	yes
PICCS (PH)	yes
EINECS	yes

## Section 16. Other information

**Disclaimer:**

This Safety Data Sheet has been generated based on Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).