



Safety Data Sheet

Page 1 of 15

LOCTITE SI 5699 GY known as LOCTITE 5699Grey 250KG
EN/CH/JP

SDS No. : 152852

V001.19

Revision: 22.02.2022

printing date: 30.05.2023

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name:

LOCTITE SI 5699 GY known as LOCTITE 5699Grey 250KG EN/CH/JP

Other means of identification:

LOCTITE SI 5699 250KGEN/CH/JPLOCTITE SI 5699 250KGEN/CH/JP

Product code:

IDH882798

Recommended use of the chemical and restrictions on use

Intended use:

Silicone sealant

Identification of manufacturer, importer or distributor

Manufacturer: Henkel Loctite (China) Co. Ltd, No. 90 Zhu Jiang Road, Yantai Economic, Technological Development Zone, 264006 Shangdong Province, China Tel: +86-535-6399803 Fax: +86-535-6371999

Importer: Henkel Thailand Ltd The Offices at Centralworld, 35th Floor, 999/9 Rama 1 Rd, Kwang Patumwan, Khet Patumwan, Bangkok 10330, Thailand. Phone : +6622098000 Fax : +6622098008

E-mail address of person responsible for Safety Data Sheet:

ap-ua-psra.sea@henkel.com

Emergency information:

FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call CHEMTREC: +1 703-741-5970

Section 2. Hazards identification

GHS Classification:

<u>Hazard Class</u>	<u>Hazard Category</u>	<u>Target organ</u>
Serious eye damage/eye irritation	Category 1	
Skin sensitizer	Category 1	
Carcinogenicity	Category 1B	
Specific target organ toxicity - single exposure	Category 2	Upper respiratory tract

GHS label elements:

Hazard pictogram:



Signal word:

Danger

Hazard statement:

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H350 May cause cancer.

H371 May cause damage to the following organs:

Precaution:

Prevention:

P201 Obtain special instructions before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P311 If exposed or concerned: Call a POISON CENTER/doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Calcium carbonate 471-34-1	10- 30 %	
Butan-2-one O,O',O''-(vinylsilylidyne)trioxime 2224-33-1	1- 10 %	Acute toxicity 5; Oral H303 Serious eye damage/eye irritation 1 H318 Skin sensitizer 1 H317 Specific target organ toxicity - repeated exposure 2 H373 Acute hazards to the aquatic environment 3 H402
2-butanone oxime 96-29-7	1- 10 %	Flammable liquids 4 H227 Acute toxicity 3; Oral H301 Acute toxicity 4; Dermal H312 Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 1 H318 Skin sensitizer 1 H317 Carcinogenicity 1B; Inhalation H350 Specific target organ toxicity - single exposure 1 H370 Specific target organ toxicity - single exposure 3 H336 Specific target organ toxicity - repeated exposure 2 H373 Acute hazards to the aquatic environment 3 H402
octamethylcyclotetrasiloxane 556-67-2	< 0.1 %	Flammable liquids 3 H226 Toxic to reproduction 2 H361 Chronic hazards to the aquatic environment 1 H410

Section 4. First aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Seek medical advice.

Ingestion:

Do not induce vomiting.
Seek medical advice.

Indication of immediate medical attention and special treatment needed:

See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media:

Carbon dioxide, foam, powder

Specific hazards arising from the chemical:

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.
Silicon dioxide

Special protection equipment and precautions for firefighters:

Wear self-contained breathing apparatus.

Additional fire fighting advice:

In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions:

Avoid contact with skin and eyes.
Wear protective equipment.
Ensure adequate ventilation.
See advice in section 8

Environmental precautions:

Do not empty into drains / surface water / ground water.

Clean-up methods:

Scrape up as much material as possible.
Sweep up spilled material. Avoid creating dust.
Store in a partly filled, closed container until disposal.
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:

Use only in well-ventilated areas.
Vapours should be extracted to avoid inhalation.
Avoid skin and eye contact.
See advice in section 8

Storage:

Store in a cool, well-ventilated place.
Refer to Technical Data Sheet
Never allow product to get in contact with water during storage

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

CALCIUM CARBONATE, INHALABLE DUST 471-34-1	Value type	Time Weighted Average (TWA):
	mg/m³	15
	Remarks	TH OEL
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles 471-34-1	Value type	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles 471-34-1	Value type	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH
CALCIUM CARBONATE, RESPIRABLE DUST 471-34-1	Value type	Time Weighted Average (TWA):
	mg/m³	5
	Remarks	TH OEL

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Protective eye equipment should conform to EN166.

Body protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

Hygienic measures:

Take off contaminated clothing and wash before reuse.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Section 9. Physical and chemical properties

Appearance:	grey paste
Odor:	odourless
Odor threshold (CA):	No data available.
pH:	Not applicable
Melting point / freezing point:	Not available.
Specific gravity:	1.5
Boiling point:	> 200 °C (> 392 °F)
Flash point:	> 93 °C (> 199.4 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure: (; 50 °C (122 °F))	< 5 mm hg
Vapor density:	No data available.
Density:	1.5 g/cm ³
Solubility:	Polymerises in presence of water.
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content: (2010/75/EC)	< 5 %

Section 10. Stability and reactivity

Reactivity/Incompatible materials:
Polymerises in presence of water.

Chemical stability:
Stable under recommended storage conditions.

Conditions to avoid:
Exposure to air or moisture over prolonged periods.
Stable

Hazardous decomposition products:
Methyl ethyl ketoxime formed during cure.
Methanol is liberated slowly upon exposure to moisture.

Section 11. Toxicological information

General toxicological information:	Methylethyl ketoxime released during polymerisation of oxime curing RTV silicones is irritating to the respiratory system Methylethyl ketoxime released during polymerisation of oxime curing silicones. It is harmful in contact with skin and is a skin sensitizer.
Oral toxicity:	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method
Dermal toxicity:	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method

Symptoms of Overexposure: After eye contact: Corrosive, may cause permanent damage to eyes (impairment of vision).
SKIN: Rash, Urticaria.

Acute oral toxicity:

Calcium carbonate 471-34-1	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 420 (Acute Oral Toxicity)
Butan-2-one O,O',O''- (vinylsilylidyne)trioxime 2224-33-1	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
Butan-2-one O,O',O''- (vinylsilylidyne)trioxime 2224-33-1	Value type	Acute toxicity estimate (ATE)
	Value	2,500 mg/kg
	Species	
	Method	Expert judgement
2-butanone oxime 96-29-7	Value type	Acute toxicity estimate (ATE)
	Value	100 mg/kg
	Species	
	Method	Expert judgement
octamethylcyclotetrasiloxane 556-67-2	Value type	LD50
	Value	> 4,800 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

Acute inhalative toxicity:

Calcium carbonate 471-34-1	Value type	LC50
	Value	> 3 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 403 (Acute Inhalation Toxicity)
octamethylcyclotetrasiloxane 556-67-2	Value type	LC50
	Value	36 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 403 (Acute Inhalation Toxicity)

Acute dermal toxicity:

Calcium carbonate 471-34-1	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
Butan-2-one O,O',O''-(vinylsilylidene)trioxime 2224-33-1	Value type	LD50
	Value	> 2,009 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
2-butanone oxime 96-29-7	Value type	Acute toxicity estimate (ATE)
	Value	1,100 mg/kg
	Species	
	Method	Expert judgement
octamethylcyclotetrasiloxane 556-67-2	Value type	LD50
	Value	> 2,375 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Calcium carbonate 471-34-1	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Butan-2-one O,O',O''-(vinylsilylidene)trioxime 2224-33-1	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
octamethylcyclotetrasiloxane 556-67-2	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Calcium carbonate 471-34-1	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2-butanone oxime 96-29-7	Result	Category 1 (irreversible effects on the eye)
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
octamethylcyclotetrasiloxane 556-67-2	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Calcium carbonate 471-34-1	Result	not sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Butan-2-one O,O',O''- (vinylsilyldiylidene)trioxime 2224-33-1	Result	Sensitizing
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
2-butanone oxime 96-29-7	Result	sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
octamethylcyclotetrasiloxane 556-67-2	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Calcium carbonate 471-34-1	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Calcium carbonate 471-34-1	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Calcium carbonate 471-34-1	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Butan-2-one O,O',O''- (vinylsilyldyne)trioxime 2224-33-1	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Butan-2-one O,O',O''- (vinylsilyldyne)trioxime 2224-33-1	Result	negative
	Type of study / Route of administration	intrapertoneal
	Metabolic activation / Exposure time	
	Species	mouse
2-butanone oxime 96-29-7	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	EPA OPPTS 870.5265 (The Salmonella typhimurium Bacterial Reverse Mutation Test)
2-butanone oxime 96-29-7	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2-butanone oxime 96-29-7	Result	negative
	Type of study / Route of administration	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro
	Metabolic activation / Exposure time	
	Method	OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
2-butanone oxime 96-29-7	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	rat
2-butanone oxime 96-29-7	Result	negative
	Type of study / Route of administration	oral: feed
	Metabolic activation / Exposure time	
	Species	Drosophila melanogaster
octamethylcyclotetrasiloxane 556-67-2	Result	negative
	Type of study / Route of administration	bacterial gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
octamethylcyclotetrasiloxane 556-67-2	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
octamethylcyclotetrasiloxane 556-67-2	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

octamethylcyclotetrasiloxane 556-67-2	Result	negative
	Type of study / Route of administration	inhalation
	Metabolic activation / Exposure time	
	Species	rat
	Method	equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
octamethylcyclotetrasiloxane 556-67-2	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	rat
	Method	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)

Repeated dose toxicity:

Calcium carbonate 471-34-1	Result	NOAEL=1,000 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	48 ddaily
	Species	rat
	Method	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Butan-2-one O,O',O''- (vinylsilyldiylidene)trioxime 2224-33-1	Result	LOAEL=40 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	13 w5 d/week
	Species	rat
	Method	EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
2-butanone oxime 96-29-7	Result	LOAEL=40 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	13 w5 d/week
	Species	rat
	Method	EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
octamethylcyclotetrasiloxane 556-67-2	Result	LOAEL=35 ppm
	Route of application	inhalation
	Exposure time / Frequency of treatment	6 h nose only inhalation5 days/week for 13 weeks
	Species	rat
	Method	OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)
octamethylcyclotetrasiloxane 556-67-2	Result	NOAEL=960 mg/kg
	Route of application	dermal
	Exposure time / Frequency of treatment	3 w5 d/w
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Section 12. Ecological information

General ecological information:

Cured Loctite products are typical polymers and do not pose any immediate environmental hazards., Do not empty into drains / surface water / ground water.

Toxicity:

Calcium carbonate 471-34-1	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Calcium carbonate 471-34-1	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Calcium carbonate 471-34-1	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h

	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	14 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Calcium carbonate 471-34-1	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge of a predominantly domestic sewage
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Butan-2-one O,O',O''- (vinylsilylidyne)trioxime 2224-33-1	Value type	LC50
	Value	> 560 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
	Value type	NOEC
	Value	50 mg/l
	Acute Toxicity Study	Fish
	Exposure time	14 d
	Species	Oryzias latipes
	Method	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)
Butan-2-one O,O',O''- (vinylsilylidyne)trioxime 2224-33-1	Value type	EC50
	Value	201 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Butan-2-one O,O',O''- (vinylsilylidyne)trioxime 2224-33-1	Value type	EC50
	Value	94 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	30 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-butanone oxime 96-29-7	Value type	LC50
	Value	320 - 1,000 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Leuciscus idus
	Method	DIN 38412-15
	Value type	NOEC
	Value	50 mg/l
	Acute Toxicity Study	Fish
	Exposure time	14 d
	Species	Oryzias latipes
	Method	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)
2-butanone oxime 96-29-7	Value type	EC50
	Value	> 500 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	EU Method C.2 (Acute Toxicity for Daphnia)
2-butanone oxime 96-29-7	Value type	EC50
	Value	11.8 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus capricornutum
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)

	Value type	NOEC
	Value	2.56 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus capricornutum
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-butanone oxime 96-29-7	Value type	EC10
	Value	177 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	17 h
	Species	
	Method	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
octamethylcyclotetrasiloxane 556-67-2	Value type	NOEC
	Value	0.0044 mg/l
	Acute Toxicity Study	Fish
	Exposure time	93 d
	Species	Salmo gairdneri (new name: Oncorhynchus mykiss)
	Method	EPA OPPTS 797.1600 (Fish Early Life Stage Toxicity Test)
	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	EPA OTS 797.1400 (Fish Acute Toxicity Test)
octamethylcyclotetrasiloxane 556-67-2	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
octamethylcyclotetrasiloxane 556-67-2	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)
	Method	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
	Value type	EC10
	Value	0.022 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)
	Method	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
octamethylcyclotetrasiloxane 556-67-2	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge
	Method	ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge)

Persistence and degradability:

Butan-2-one O,O',O"- (vinylsilylidine)trioxime 2224-33-1	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	26 %
	Method	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
2-butanone oxime 96-29-7	Result	inherently biodegradable
	Route of application	aerobic
	Degradability	70 %
	Method	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
octamethylcyclotetrasiloxane 556-67-2	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	3.7 %
	Method	OECD Guideline 310 (Ready Biodegradability CO ₂ in Sealed Vessels (Headspace Test))

Bioaccumulative potential / Mobility in soil:

Calcium carbonate 471-34-1	LogPow	-2.12
	Temperature	
	Method	not specified
2-butanone oxime 96-29-7	Bioconcentration factor (BCF)	0.5 - 0.6
	Exposure time	42 d
	Species	Oryzias latipes
	Temperature	25 °C
	Method	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)
2-butanone oxime 96-29-7	LogPow	0.65
	Temperature	25 °C
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
octamethylcyclotetrasiloxane 556-67-2	Bioconcentration factor (BCF)	12,400
	Exposure time	28 d
	Species	Pimephales promelas
	Temperature	
	Method	EPA OTS 797.1520 (Fish Bioconcentration Test-Rainbow Trout)
octamethylcyclotetrasiloxane 556-67-2	LogPow	6.488
	Temperature	25.1 °C
	Method	OECD Guideline 123 (Partition Coefficient (1-Octanol / Water), Slow-Stirring Method)

Section 13. Disposal considerations

Product

Method of disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Collection and delivery to recycling enterprise or other registered elimination institution.

Packaging

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:

Not dangerous goods

Railroad transport RID:

Not dangerous goods

Inland water transport ADN:

Not dangerous goods

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

Section 15. Regulatory information

Regulatory Information:

Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

Global inventory status:

Regulatory list	Notification
TSCA	yes
DSL	yes
KECI (KR)	yes
ISHL (JP)	yes
IECSC	yes
AIIC	yes
NZIOC	yes
TCSI	yes
PICCS (PH)	yes
CH INV	yes
EINECS	yes

Section 16. Other information

Disclaimer:

This Safety Data Sheet has been generated based on Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance. This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).