

# **Safety Data Sheet**

Page 1 of 14

SDS No.: 150233

V001.20

Revision: 12.01.2025 printing date: 17.06.2025

# Section 1. Identification of the substance/preparation and of the company/undertaking

**Product name:** 

LOCTITE 242 BO250ML EN/CH/JP/KR

LOCTITE 242 BO250ML EN/CH/JP/KR

Other means of identification:

LOCTITE 242 BO250ML EN/CH/JP/KR

**Product code:** 

IDH235195

Recommended use of the chemical and restrictions on use

**Intended use:** 

Adhesive

Manufacturer/Importer/Distributor Representative Company

Henkel Thailand Ltd. The Offices at Centralworld,

35th Floor, 999/9 Rama 1 Rd., Kwang Patumwan, Khet Patumwan,

10330 Bangkok

Thailand

Phone: +66 (2209) 8000 Fax-no.: +66 (2209) 8008

E-mail address of person responsible for Safety Data Sheet:

ap-ua-psra.sea@henkel.com

**Emergency Telephone for Chemical Accidents:** 

FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +662 209 8008

# Section 2. Hazards identification

## **GHS Classification:**

<u>Hazard Class</u> <u>Hazard Category</u> <u>Target organ</u>

Serious eye damage/eye irritation Category 2
Specific target organ toxicity - Category 3

gory 3 respiratory tract irritation

## **GHS** label elements:

## Hazard pictogram:

single exposure



Signal word:

Warning

V001.20

#### **Hazard statement:**

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

#### **Precaution:**

#### **Prevention:**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

## Response:

P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

## Storage:

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

#### Disposal:

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

## Section 3. Composition / information on ingredients

## **Substance or Mixture:**

Mixture

## **Declaration of hazardous chemical:**

Hazard component CAS-No.	Content	GHS Classification
Silica, amorphous, fumed, crystfree 112945-52-5	1- 10 %	
α, α-dimethylbenzyl hydroperoxide	1- 10 %	Flammable liquids 4
80-15-9		H227 Organic peroxides E
		H242 Acute toxicity 4; Oral
		H302
		Acute toxicity 2; Inhalation H330
		Acute toxicity 4; Dermal H312
		Skin corrosion/irritation 1
		H314 Specific target organ toxicity - single exposure 3 H335
		Specific target organ toxicity - repeated exposure 2 H373
		Acute hazards to the aquatic environment 2 H401
		Chronic hazards to the aquatic environment 2 H411
N,N-Diethyl-p-toluidine	0.1- 1 %	Flammable liquids 4
613-48-9		H227 Acute toxicity 3; Oral
		H301 Acute toxicity 3; Inhalation
		H331
		Acute toxicity 3; Dermal H311
		Skin corrosion/irritation 2 H315
		Specific target organ toxicity - repeated exposure 2
		H373 Acute hazards to the aquatic environment 3 H402
		Chronic hazards to the aquatic environment 3 H412
methacrylic acid 79-41-4	0.1- 1 %	Flammable liquids 4 H227
77-41-4		Acute toxicity 4; Oral
		H302 Acute toxicity 4; Inhalation
		H332
		Acute toxicity 3; Dermal H311
		Skin corrosion/irritation 1 H314
		Serious eye damage/eye irritation 1
		H318 Specific target organ toxicity - single exposure 3 H335
		Acute hazards to the aquatic environment 3 H402
1,4-Naphthalenedione 130-15-4	< 0.1 %	Acute toxicity 3; Oral H301
		Acute toxicity 1; Inhalation H330
		Skin corrosion/irritation 1
		H314 Serious eye damage/eye irritation 1
		H318 Skin sensitizer 1
		H317 Specific target organ toxicity - single exposure 3
		H335 Acute hazards to the aquatic environment 1
		H400

	ronic hazards to the aquatic environment 1
	H410

## Section 4. First aid measures

#### Inhalation:

Should not be a problem as product is of low volatility. However, if feeling unwell remove patient to fresh air.

### Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

#### Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

#### Ingestion

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

## Indication of immediate medical attention and special treatment needed:

See section: Description of first aid measures

## Section 5. Fire fighting measures

## Suitable extinguishing media:

Carbon dioxide, foam, powder

## Improper extinguishing media:

High pressure waterjet

## Specific hazards arising from the chemical:

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

## Special protection equipment and precautions for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

## **Hazardous combustion products:**

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

## Additional fire fighting advice:

In case of fire, keep containers cool with water spray.

## Section 6. Accidental release measures

## Personal precautions:

Ensure adequate ventilation.

Wear protective equipment.

Avoid contact with skin and eyes.

See advice in section 8

#### **Environmental precautions:**

Do not empty into drains / surface water / ground water.

## Clean-up methods:

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

# Section 7. Handling and storage

#### Handling:

Use only in well-ventilated areas. Avoid skin and eye contact. See advice in section 8

### Storage:

Refer to Technical Data Sheet.

## Section 8. Exposure controls / personal protection

#### Components with specific control parameters for workplace:

Particles (insoluble or poorly soluble) not otherwise specified, respirable particles 112945-52-5	Value type	Time Weighted Average (TWA):
	mg/m <sup>3</sup>	3
	Remarks	ACGIH
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles 112945-52-5	Value type	Time Weighted Average (TWA):
	mg/m <sup>3</sup>	10
	Remarks	ACGIH

## Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

### Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

### Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

## **Body protection:**

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

## LOCTITE 242 BO250ML EN/CH/JP/KR

### **Engineering controls:**

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

## General protection and hygiene measures:

The workplace should be equipped with an emergency shower and eye-rinsing facility.

#### Hygienic measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Take off contaminated clothing and wash before reuse.

# Section 9. Physical and chemical properties

**Appearance:** Blue liquid

Odor: mild

Odor threshold (CA): No data available.

**pH:** Not applicable, Product is non-polar/aprotic.

Melting point / freezing point: Not applicable, Product is a liquid

Specific gravity: 1.1

**Boiling point:** > 150 °C (> 302 °F) **Flash point:** > 100 °C (> 212 °F)

(Tagliabue closed cup)

Evaporation rate:
No data available.
Flammability (solid, gas):
No data available.
Lower explosive limit:
2.6 %(V)
Upper explosive limit:
12.5 %(V)
Vapor pressure:
(; 27 °C (80.6 °F); 20 °C (68 °F))
< 0.13 mbar

Vapor density: > 1

Density:1.1 g/cm3Solubility:Slightly solublePartition coefficient: n-No data available.

octanol/water:

Auto ignition:No data available.Decomposition temperature:No data available.

Viscosity: 800 - 1,600 mPa.s (BROOKFIELD WITH HELIPATH; Instrument: RVF, HELIPATH; 25

°C (77 °F); speed of rotation: 20 min-1; Spindle No: 3; Method: ;; LCT STM 10;

Viscosity Brookfield)

**VOC content:** < 3 %

(2010/75/EC)

## Section 10. Stability and reactivity

## Reactivity/Incompatible materials:

None if used properly.

## Chemical stability:

Stable under recommended storage conditions.

#### **Conditions to avoid:**

Stable under normal conditions of storage and use.

## Hazardous decomposition products:

None if used for intended purpose.

# Section 11. Toxicological information

**Oral toxicity:** Acute toxicity estimate (ATE) : > 2,000 mg/kg

Method: Calculation method

**Inhalative toxicity:** Acute toxicity estimate (ATE) : > 20 mg/l

Exposure time: 4 h Test atmosphere: Vapor. Method: Calculation method

**Dermal toxicity:** Acute toxicity estimate (ATE) : > 2,000 mg/kg

Method: Calculation method

Symptoms of Overexposure: EYE: Irritation, conjunctivitis.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

Prolonged or repeated contact may cause skin irritation.

## Acute oral toxicity:

Silica, amorphous, fumed, cryst	Value type	LD50
free	Value	> 5,000 mg/kg
112945-52-5	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
α, α-dimethylbenzyl hydroperoxide	Value type	LD50
80-15-9	Value	382 mg/kg
	Species	rat
	Method	other guideline:
N,N-Diethyl-p-toluidine	Value type	Acute toxicity estimate (ATE)
613-48-9	Value	100 mg/kg
	Species	
	Method	Expert judgement
methacrylic acid	Value type	LD50
79-41-4	Value	1,320 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
1,4-Naphthalenedione	Value type	LD50
130-15-4	Value	124 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

# Acute inhalative toxicity:

Silica, amorphous, fumed, cryst	Value type	LC0
free	Value	0.139 mg/l
112945-52-5	Exposure time	4 h
	Species	rat
	Method	not specified
α, α-dimethylbenzyl hydroperoxide	Value type	LC50
80-15-9	Value	1.370 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified
N,N-Diethyl-p-toluidine	Value type	Acute toxicity estimate (ATE)
613-48-9	Value	3 mg/l
	Exposure time	
	Species	
	Method	Expert judgement
methacrylic acid	Value type	LC50
79-41-4	Value	3.19 - 6.5 mg/l
	Exposure time	4 h
	Species	rat
	Method	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
methacrylic acid	Value type	Acute toxicity estimate (ATE)
79-41-4	Value	3.19 mg/l
	Exposure time	
	Species	
	Method	Expert judgement
1,4-Naphthalenedione	Value type	LC50
130-15-4	Value	0.046 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 403 (Acute Inhalation Toxicity)

# Acute dermal toxicity:

Silica, amorphous, fumed, cryst	Value type	LD50
free	Value	> 2,000 mg/kg
112945-52-5	Species	rabbit
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
α, α-dimethylbenzyl hydroperoxide	Value type	Acute toxicity estimate (ATE)
80-15-9	Value	1,100 mg/kg
	Species	
	Method	Expert judgement
N,N-Diethyl-p-toluidine	Value type	Acute toxicity estimate (ATE)
613-48-9	Value	300 mg/kg
	Species	
	Method	Expert judgement
methacrylic acid	Value type	LD50
79-41-4	Value	500 - 1,000 mg/kg
	Species	rabbit
	Method	Dermal Toxicity Screening
methacrylic acid	Value type	Acute toxicity estimate (ATE)
79-41-4	Value	500 mg/kg
	Species	
	Method	Expert judgement

# Skin corrosion/irritation:

Silica, amorphous, fumed, crystfree	Result	not irritating
112945-52-5	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
α, α-dimethylbenzyl hydroperoxide	Result	corrosive
80-15-9	Exposure time	
	Species	rabbit
	Method	Draize Test
N,N-Diethyl-p-toluidine	Result	irritating

613-48-9	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
methacrylic acid	Result	corrosive
79-41-4	Exposure time	3 min
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1,4-Naphthalenedione	Result	Category 1C (corrosive)
130-15-4	Exposure time	
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

# Serious eye damage/irritation:

Silica, amorphous, fumed, crystfree	Result	not irritating
112945-52-5	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
methacrylic acid	Result	corrosive
79-41-4	Exposure time	
	Species	rabbit
	Method	Draize Test

# Respiratory or skin sensitization:

methacrylic acid	Result	not sensitising
79-41-4	Test type	Buehler test
	Species	guinea pig
	Method	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
1,4-Naphthalenedione	Result	sensitising
130-15-4	Test type	not specified
	Species	guinea pig
	Method	not specified

# LOCTITE 242 BO250ML EN/CH/JP/KR

# Germ cell mutagenicity:

Silica, amorphous, fumed, cryst	Result	negative
free	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
112945-52-5	Metabolic activation / Exposure time	• • • • • • • • • • • • • • • • • • • •
	Method	not specified
Silica, amorphous, fumed, cryst	Result	negative
free	Type of study / Route of administration	in vitro mammalian chromosome aberration test
112945-52-5	Metabolic activation / Exposure time	
	Method	not specified
Silica, amorphous, fumed, cryst	Result	negative
free 112945-52-5	Type of study / Route of administration	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro
	Metabolic activation / Exposure time	
	Method	not specified
α, α-dimethylbenzyl	Result	positive
hydroperoxide	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
80-15-9	Metabolic activation / Exposure time	without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
α, α-dimethylbenzyl	Result	negative
hydroperoxide	Type of study / Route of administration	dermal
80-15-9	Metabolic activation / Exposure time	
	Species	mouse
	Method	not specified
methacrylic acid	Result	negative
79-41-4	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 471 (Bacterial
		Reverse Mutation Assay)
methacrylic acid	Result	negative
79-41-4	Type of study / Route of administration	inhalation
	Metabolic activation / Exposure time	
	Species	mouse
	Method	equivalent or similar to OECD Guideline 478 (Genetic
		Toxicology: Rodent Dominant Lethal Test)
methacrylic acid	Result	negative
79-41-4	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	equivalent or similar to OECD Guideline 474
		(Mammalian Erythrocyte Micronucleus Test)

# Repeated dose toxicity:

α, α-dimethylbenzyl	Result	
hydroperoxide	Route of application	inhalation: aerosol
80-15-9	Exposure time / Frequency of treatment	6 h/d5 d/w
	Species	rat
	Method	not specified
methacrylic acid	Result	
79-41-4	Route of application	inhalation
	Exposure time / Frequency of treatment	90 d6 h/d, 5 d/w
	Species	rat
	Method	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-
		Day)

# **Section 12. Ecological information**

General ecological information:

Do not empty into drains / surface water / ground water.

Page 11 of 14

SDS No.: 150233 V001.20

# LOCTITE 242 BO250ML EN/CH/JP/KR

# **Ecotoxicity:**

# Toxicity:

Cilias amorrhaus fun-1	Valua typa	T C50
Silica, amorphous, fumed, cryst free	Value type Value	LC50
	Acute Toxicity Study	> 10,000 mg/l
112945-52-5		Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio) OECD Guideline 203 (Fish, Acute Toxicity Test)
	Method	
α, α-dimethylbenzyl hydroperoxide	Value type	LC50
80-15-9	Value	3.9 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
α, α-dimethylbenzyl hydroperoxide	Value type	EC50
80-15-9	Value	18.84 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
α, α-dimethylbenzyl hydroperoxide	Value type	EC50
80-15-9	Value	3.1 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	1 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
α, α-dimethylbenzyl hydroperoxide	Value type	EC10
80-15-9	Value	70 mg/l
00 10 7	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	not specified
	Method	not specified
N,N-Diethyl-p-toluidine	Value type	LC50
613-48-9	Value type Value	78.62 mg/l
013-48-9	Acute Toxicity Study	Fish
	1 1	96 h
	Exposure time Species	Danio rerio
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
NINID' d. 1. (1'1'		
N,N-Diethyl-p-toluidine 613-48-9	Value type	EC50
013-48-9	Value	10.34 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
N,N-Diethyl-p-toluidine	Value type	EC50
613-48-9	Value	23.69 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
methacrylic acid	Value type	LC50
79-41-4	Value	85 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Salmo gairdneri (new name: Oncorhynchus mykiss)
	Method	EPA OTS 797.1400 (Fish Acute Toxicity Test)
	Value type	NOEC
	Value	10 mg/l
	Acute Toxicity Study	Fish
	Exposure time	35 d
	Species	Danio rerio

	Method	OECD Guideline 210 (fish early lite stage toxicity test)
methacrylic acid	Value type	EC50
79-41-4	Value	> 130 mg/l
77-1-4	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test,
		Freshwater Daphnids)
methacrylic acid	Value type	NOEC
79-41-4	Value	8.2 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC50
	Value	45 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
methacrylic acid	Value type	EC10
79-41-4	Value	100 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	17 h
	Species	Pseudomonas putida
	Method	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
1,4-Naphthalenedione	Value type	LC50
130-15-4	Value	0.045 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oryzias latipes
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,4-Naphthalenedione	Value type	EC50
130-15-4	Value	0.026 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,4-Naphthalenedione	Value type	NOEC
130-15-4	Value	0.07 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC50
	Value	0.42 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,4-Naphthalenedione	Value type	EC50
130-15-4	Value	5.94 mg/l
130-13-4	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge of a predominantly domestic sewage
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

# Persistence and degradability:

α, α-dimethylbenzyl	Result	not readily biodegradable.
hydroperoxide	Route of application	aerobic
80-15-9	Degradability	3 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
N,N-Diethyl-p-toluidine	Result	not readily biodegradable.
613-48-9	Route of application	not specified
	Degradability	1 %
	Method	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
methacrylic acid 79-41-4	Result	readily biodegradable
	Route of application	aerobic

## LOCTITE 242 BO250ML EN/CH/JP/KR

	Degradability	86 %
	Method	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
	Result	inherently biodegradable
	Route of application	aerobic
	Degradability	100 %
	Method	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA
		Test)
1,4-Naphthalenedione	Result	not readily biodegradable.
130-15-4	Route of application	aerobic
	Degradability	0 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry
		Test)

## Bioaccumulative potential / Mobility in soil:

α, α-dimethylbenzyl	Bioconcentration factor (BCF)	9.1
hydroperoxide	Exposure time	
80-15-9	Species	calculation
	Temperature	
	Method	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
α, α-dimethylbenzyl	LogPow	1.6
hydroperoxide	Temperature	25 °C
80-15-9	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
N,N-Diethyl-p-toluidine 613-48-9	LogPow	3.7
	Temperature	
	Method	QSAR (Quantitative Structure Activity Relationship)
methacrylic acid 79-41-4	LogPow	0.93
	Temperature	22 °C
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
1,4-Naphthalenedione 130-15-4	LogPow	1.71
	Temperature	
	Method	not specified

# Section 13. Disposal considerations

## **Product**

## Method of disposal:

Dispose of in accordance with local and national regulations.

## **Packaging**

## Disposal of uncleaned packages:

Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

# **Section 14. Transport information**

## Road transport ADR:

Not dangerous goods

## Railroad transport RID:

Not dangerous goods

### **Inland water transport ADN:**

Not dangerous goods

## **Marine transport IMDG:**

Not dangerous goods

## Air transport IATA:

Not dangerous goods

## Section 15. Regulatory information

## **Regulatory Information:**

Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

## Global inventory status:

Regulatory list	Notification
TSCA	yes
DSL	yes
KECI (KR)	yes
ENCS (JP)	yes
ISHL (JP)	yes
IECSC	yes
AIIC	yes
NZIOC	yes
TCSI	yes
PICCS (PH)	yes

## Section 16. Other information

## Disclaimer:

This Safety Data Sheet has been generated based on Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).