

Safety Data Sheet

LOCTITE 262

Page 1 of 14

SDS No.: 153483

V001.12 Revision: 22.12.2021

printing date: 20.05.2022

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name:

LOCTITE 262

Other means of identification:

LOCTITE 262 BO50MLEN/CH/JPLOCTITE 262 BO50MLEN/CH/JP

Product code:

IDH232073

Recommended use of the chemical and restrictions on use

Intended use:

Anaerobic Adhesive

Identification of manufacturer, importer or distributor

Manufacturer: Henkel Puerto Rico, Inc., 9 V. Quilinchini Avenue, 00637 Sabana Grande, Puerto Rico. Phone: 001 787 873 6500 Fax: 001 787 873 2619

Importer: Henkel Thailand Ltd The Offices at Centralworld, 35th Floor, 999/9 Rama 1 Rd, Kwang Patumwan, Khet Patumwan, Bangkok 10330, Thailand. Phone: + 6622098000 Fax: +6622098008

E-mail address of person responsible for Safety Data Sheet:

ap-ua-psra.sea@henkel.com

Emergency information:

FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call CHEMTREC: +1 703-741-5970

Section 2. Hazards identification

GHS Classification:

Hazard Class Hazard Category Serious eye damage/eye irritation

Specific target organ toxicity -

Category 2

Category 3

Target organ

respiratory tract irritation

GHS label elements:

Hazard pictogram:



single exposure

Page 2 of 14 SDS No.: 153483 **LOCTITE 262**

V001.12

Signal word:

Warning

Hazard statement:

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Precaution:

Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal:

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Page 3 of 14 SDS No.: 153483 LOCTITE 262

V001.12

Section 3. Composition / information on ingredients

Substance or Mixture:

Mixture

Declaration of hazardous chemical:

Content	GHS Classification
1- 10 %	
1- 10 %	Flammable liquids 4
	H227 Organic peroxides E H242
	Acute toxicity 4; Oral H302
	Acute toxicity 2; Inhalation H330
	Acute toxicity 4; Dermal H312
	Skin corrosion/irritation 1 H314
	Specific target organ toxicity - single exposure 3 H335
	Specific target organ toxicity - repeated exposure 2 H373
	Acute hazards to the aquatic environment 2 H401
	Chronic hazards to the aquatic environment 2 H411
0.1- 1 %	Acute toxicity 3; Oral H301
	Acute toxicity 3; Inhalation H331
	Acute toxicity 3; Dermal H311
	Specific target organ toxicity - repeated exposure 2 H373
	Acute hazards to the aquatic environment 3 H402
	Chronic hazards to the aquatic environment 3 H412
0.1- 1 %	Flammable liquids 2 H225
	Acute toxicity 5; Inhalation H333
	Skin corrosion/irritation 2 H315
	Skin sensitizer 1B H317
	Specific target organ toxicity - single exposure 3 H335
	Acute hazards to the aquatic environment 3 H402
< 0.1 %	Acute toxicity 3; Oral H301
	Acute toxicity 1; Inhalation H330
	Skin corrosion/irritation 1 H314
	Serious eye damage/eye irritation 1 H318
	Skin sensitizer 1 H317
	Specific target organ toxicity - single exposure 3 H335
	Acute hazards to the aquatic environment 1 H400
	Chronic hazards to the aquatic environment 1 H410
	1- 10 % 1- 10 % 0.1- 1 %

Page 4 of 14 SDS No.: 153483 **LOCTITE 262**

V001.12

Section 4. First aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Rinse with running water and soap.

Seek medical advice.

Eve contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

Indication of immediate medical attention and special treatment needed:

See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media:

Carbon dioxide, foam, powder

Improper extinguishing media:

High pressure waterjet

Specific hazards arising from the chemical:

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

Special protection equipment and precautions for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional fire fighting advice:

In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions:

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

See advice in section 8

Environmental precautions:

Do not empty into drains / surface water / ground water.

Clean-up methods:

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

Page 5 of 14 SDS No.: 153483 **LOCTITE 262**

V001.12

Section 7. Handling and storage

Handling:

Use only in well-ventilated areas.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

See advice in section 8

Storage:

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

Refer to Technical Data Sheet

Page 6 of 14 SDS No.: 153483 **LOCTITE 262**

V001.12

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

PARTICLES (INSOLUBLE OR POORLY SOLUBLE) NOT OTHERWISE SPECIFIED, INHALABLE PARTICLES 9002-88-4	Value type	Time Weighted Average (TWA):
	mg/m ³	10
	Remarks	ACGIH
PARTICLES (INSOLUBLE OR POORLY SOLUBLE) NOT OTHERWISE SPECIFIED, RESPIRABLE PARTICLES 9002-88-4	Value type	Time Weighted Average (TWA):
	mg/m ³	3
	Remarks	ACGIH
METHYLMETHACRYLATE 80-62-6	Value type	Time Weighted Average (TWA):
	ppm	50
	Remarks	ACGIH
METHYLMETHACRYLATE 80-62-6	Value type	Time Weighted Average (TWA):
	ppm	100
	Remarks	THOEL
METHYLMETHACRYLATE 80-62-6	Value type	Short Term Exposure Limit (STEL):
	ppm	100
	Remarks	ACGIH

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Protective eye equipment should conform to EN166.

Body protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

Hygienic measures:

Take off contaminated clothing and wash before reuse.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

SDS No.: 153483 Page 7 of 14

V001.12 LOCTITE 262

Section 9. Physical and chemical properties

Appearance: red liquid
Odor: characteristic
Odor threshold (CA): No data available

Odor threshold (CA): No data available.

pH: No applicable, Mixture reacts with water.

Melting point / freezing point:

No data available.

Specific gravity: 1.05

Boiling point: > 150 °C (> 302 °F) **Flash point:** > 93.3 °C (> 199.94 °F)

(Tagliabue closed cup)

Evaporation rate:

Flammability (solid, gas):

Lower explosive limit:

Upper explosive limit:

Vapor pressure:

No data available.

No data available.

Vo data available.

Vo data available.

(; 20.0 °C (68 °F))

Vapor density:No data available.Density:1.05 g/mlSolubility:Slightly solublePartition coefficient: n-No data available.

octanol/water:

Auto ignition:No data available.Decomposition temperature:No data available.Viscosity:No data available.

VOC content: < 3 %

(2010/75/EC)

Section 10. Stability and reactivity

Reactivity/Incompatible materials:

Peroxides.

Chemical stability:

Stable under recommended storage conditions.

Conditions to avoid:

Stable

Section 11. Toxicological information

Oral toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg

Method: Calculation method

Inhalative toxicity: Acute toxicity estimate (ATE) : > 20 mg/l

Exposure time: 4 h
Test atmosphere: Vapor.
Method: Calculation method

Dermal toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg

Method: Calculation method

Page 8 of 14 SDS No.: 153483 LOCTITE 262

V001.12

Symptoms of Overexposure:

EYE: Irritation, conjunctivitis.
RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.
Prolonged or repeated contact may cause skin irritation.

Acute oral toxicity:

Ethene, homopolymer	Value type	Acute toxicity estimate (ATE)
9002-88-4	Value	>5,000 mg/kg
	Species	
	Method	Expert judgement
α, α-dimethylbenzyl hydroperoxide	Value type	LD50
80-15-9	Value	382 mg/kg
	Species	rat
	Method	other guideline:
methyl methacrylate	Value type	LD50
80-62-6	Value	9,400 mg/kg
80-62-6	Value Species	9,400 mg/kg rat
80-62-6		
1,4-Naphthalenedione	Species	rat
	Species Method	rat not specified
1,4-Naphthalenedione	Species Method Value type	rat not specified LD50

Page 9 of 14 SDS No.: 153483 LOCTITE 262

V001.12

Acute inhalative toxicity:

Ethene, homopolymer	Value type	Acute toxicity estimate (ATE)
9002-88-4	Value	> 5 mg/l
	Exposure time	
	Species	
	Method	Expert judgement
α, α-dimethylbenzyl hydroperoxide	Value type	LC50
80-15-9	Value	1.370 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified
methyl methacrylate	Value type	LC50
methyl methacrylate 80-62-6	Value type Value	LC50 29.8 mg/l
	* *	
	Value	29.8 mg/l 4 h rat
	Value Exposure time	29.8 mg/l 4 h
	Value Exposure time Species	29.8 mg/l 4 h rat
80-62-6	Value Exposure time Species Method	29.8 mg/l 4 h rat not specified
80-62-6 1,4-Naphthalenedione	Value Exposure time Species Method Value type	29.8 mg/l 4 h rat not specified LC50
80-62-6 1,4-Naphthalenedione	Value Exposure time Species Method Value type Value	29.8 mg/l 4 h rat not specified LC50 0.046 mg/l

Acute dermal toxicity:

Ethene, homopolymer	Value type	Acute toxicity estimate (ATE)
9002-88-4	Value	> 5,000 mg/kg
	Species	
	Method	Expert judgement
α, α-dimethylbenzyl hydroperoxide	Value type	Acute toxicity estimate (ATE)
80-15-9	Value	1,100 mg/kg
	Species	
	Method	Expert judgement
methyl methacrylate	Value type	LD50
80-62-6	Value	> 5,000 mg/kg
	Species	rabbit
	Method	not specified

Skin corrosion/irritation:

α, α-dimethylbenzyl hydroperoxide	Result	corrosive
80-15-9	Exposure time	
	Species	rabbit
	Method	Draize Test
1,4-Naphthalenedione	Result	Category 1C (corrosive)
130-15-4	Exposure time	
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Ethene, homopolymer	Result	not irritating
9002-88-4	Exposure time	24 h
	Species	rabbit
	Method	FDA Guideline

Page 10 of 14 SDS No.: 153483 LOCTITE 262

V001.12

Respiratory or skin sensitization:

Ethene, homopolymer	Result	not sensitising
9002-88-4	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
methyl methacrylate	Result	sensitising
80-62-6	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
1,4-Naphthalenedione	Result	sensitising
130-15-4	Test type	not specified
	Species	guinea pig
	Method	not specified

Germ cell mutagenicity:

Ethene, homopolymer	Result	negative
9002-88-4	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	Ames Test
α, α-dimethylbenzyl	Result	positive
hydroperoxide	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
80-15-9	Metabolic activation / Exposure time	without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
α, α-dimethylbenzyl	Result	negative
hydroperoxide	Type of study / Route of administration	dermal
80-15-9	Metabolic activation/Exposure time	
	Species	mouse
	Method	not specified
methyl methacrylate	Result	negative
80-62-6	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	not specified

Repeated dose toxicity:

α, α-dimethylbenzyl	Result	
hydroperoxide	Route of application	inhalation: aerosol
80-15-9	Exposure time / Frequency of treatment	6 h/d5 d/w
	Species	rat
	Method	not specified
methyl methacrylate	Result	LOAEL=2000ppm
80-62-6	Route of application	inhalation
	Exposure time / Frequency of treatment	14 weeks6 hrs/day, 5 days/wk
	Species	mouse
	Method	Dose Range Finding Study
methyl methacrylate	Result	NOAEL=1000 ppm
80-62-6	Route of application	inhalation
	Exposure time / Frequency of treatment	14 weeks6 hrs/day, 5 days/wk
	Species	mouse
	Method	Dose Range Finding Study

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Toxicity:

Ethene, homopolymer	Value type	LC50
9002-88-4	Value	> 100 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Leuciscus idus
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethene, homopolymer	Value type	EC0
9002-88-4	Value	> 1,000 mg/l

	Acute Toxicity Study	Bacteria
	Exposure time	3 h
		not specified
11. 11	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
α , α -dimethylbenzyl hydroperoxide		LC50
80-15-9	Value	3.9 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
α, α-dimethylbenzyl hydroperoxide	Value type	EC50
80-15-9	Value	18.84 mg/l
0.000		Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
F (1. 11 11. 1		
α , α -dimethylbenzyl hydroperoxide		EC50
80-15-9	Value	3.1 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	1 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
		Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
a a dimathalbangal badananayida		EC10
α, α-dimethylbenzyl hydroperoxide 80-15-9		
80-13-9	Value	70 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	
		not specified
methyl methacrylate	J I	LC50
80-62-6	Value	350 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Leuciscus idus
	1	OECD Guideline 203 (Fish, Acute Toxicity Test)
methyl methacrylate		EC50
80-62-6	J 1	69 mg/l
00 02 0		Daphnia
	Exposure time	48 h
		Daphnia magna
		EPA OT \$797.1300 (Aquatic Invertebrate Acute Toxicity Test,
		Freshwater Daphnids)
methyl methacrylate	71	EC50
80-62-6	Value	170 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Selenastrum capricomutum (new name: Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Selenastrum capricomutum (new name: Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
methyl methacrylate	Value type	EC20
80-62-6	Value	> 150 - 200 mg/l
	, ,	Bacteria
	Exposure time	30 min
	Species	activated sludge, domestic
		ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated
		Sludge)
1,4-Naphthalenedione	Value type	LC50
130-15-4	Value	0.045 mg/l
150 15 1		Fish
	product officity Diddy	F
		96 h
	Exposure time Species	96 h Oryzias latipes

SDS No.: 153483 V001.12 LOCTITE 262

	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,4-Naphthalenedione	Value type	EC50
130-15-4	Value	0.026 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,4-Naphthalenedione	Value type	NOEC
130-15-4	Value	0.07 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	P seudo kirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC50
	Value	0.42 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,4-Naphthalenedione	Value type	EC50
130-15-4	Value	5.94 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge of a predominantly domestic sewage
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

Persistence and degradability:

Ethene, homopolymer	Result	not readily biodegradable.
9002-88-4	Route of application	aerobic
	Degradability	1 %
	Method	ISO 10708 (BODIS-Test)
α, α-dimethylbenzyl	Result	not readily biodegradable.
hydroperoxide	Route of application	aerobic
80-15-9	Degradability	3 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
methyl methacrylate	Result	readily biodegradable
80-62-6	Route of application	aerobic
	Degradability	94 %
	Method	OECD Guideline 301 C (Ready Biodegradability: Modified MITITest (I))
1,4-Naphthalenedione 130-15-4	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	0 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry
		Test)

Bioaccumulative potential / Mobility in soil:

α, α-dimethylbenzyl	Bioconcentration factor (BCF)	9.1
hydroperoxide	Exposure time	
80-15-9	Species	calculation
	Temperature	
	Method	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	LogPow	1.6
	Temperature	25 °C
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
		Method)
methyl methacrylate 80-62-6	LogPow	1.38
	Temperature	20 °C
	Method	other guideline:
1,4-Naphthalenedione 130-15-4	LogPow	1.71
	Temperature	
	Method	not specified

SDS No.: 153483 Page 13 of 14

V001.12 LOCTITE 262

Section 13. Disposal considerations

Product

Method of disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Packaging

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:

Not dangerous goods

Railroad transport RID:

Not dangerous goods

Inland water transport ADN:

Not dangerous goods

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

Section 15. Regulatory information

Regulatory Information:

Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

Global inventory status:

Regulatory list	Notification
TSCA	yes
DSL	yes
KECI (KR)	yes
ENCS (JP)	yes
ISHL (JP)	yes
IECSC	yes
AIIC	yes
NZIOC	yes
TCSI	yes
PICCS (PH)	yes
CH INV	yes
EINECS	yes

Page 14 of 14 SDS No.: 153483 **LOCTITE 262**

V001.12

Section 16. Other information

Disclaimer:

This Safety Data Sheet has been generated based on Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance. Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.